**Colour MFP** 

# **MP C501SP**





# Do more, faster - from start to finish

Accelerate business efficiency with this high-end smart MFP designed to help you get more done. The MP C501SP offers an impressive 50ppm print speed, high paper capacity, integrated finishing capability and renowned durability. Ready to operate in just 1.0 seconds, and easy to use with a 10.1 inch Smart Operation Panel (SOP) featuring Ricoh Smart Integration. That means your device is always at the cutting edge of functionality with pre-installed apps, or ready to download from the cloud for more efficient workflows.

- 50ppm print speed
- · Internal finisher capability
- · Access to cloud-based apps and solutions



# Do more - work together

The MP C501SP makes the most of your investment in Ricoh equipment, pairing with other Ricoh machines for unified compatibility, including a common interface. Boost productivity with shared, easy to use apps and mobile connectivity to print, copy or scan from and to Smart Devices.



## **Productivity under pressure**

Refinements such as an internal finishing capability mean you can trust this MFP to keep on working for you through the heaviest workloads. Its value-added productivity features include advanced paper output via sort, stack and staple functions as well as double-sided scanning.



# Work sustainably

The MP C501SP is designed with sustainability in mind. Energy-saving technologies mean it consumes notably less power than many other models on the market. Saving energy is great for business, reducing operating costs and providing a powerful support for your business' performance .



### **MP C501SP**

MAIN SPECIFICATIONS

#### GENERAL

24 Warm-up time (sec.) First output speed: B/W (sec.) 4 First output speed: FC (sec.) 5.7 Continuous output speed (ppm) 50 Weight (kg) 103.4 Dimensions: W x D x H (mm) 587 x 685 x 963 Power source 220 - 240 V, 50/60 Hz



Dry electrostatic transfer system with dual component development; 4-drum method Copying process Multiple copying Up to 999 copies Resolution 600 dpi/4 bit

#### PRINTER

PCL5c, PCL6(XL), PostScript 3 (emulation), PDF direct (emulation) Printer language: standard Printer language: option Genuine Adobe ®PostScript®3™, XPS, PictBridge, PDF Direct from Adobe® Print resolution: maximum (dpi) 1,200 x 1,200/2 bit Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A Network interface: standard Network interface: option Bi-directional IEEE 1284/ECP, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, USB 2.0 Wireless, Additional NIC (2nd port) Windows® environments Windows® 7/8.1/10, Windows® Server 2008/2012/2012R2/2016 Mac OS environments Macintosh OS X v10.10 or later UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX, XenDesktop, Citrix XenApp **UNIX** environments SAP® environments SAP® R/3®, SAP® S/4®

#### SCANNER

Max. 110 (simplex)/180 (duplex) Scanning (ipm) 1,200

Resolution: maximum (dpi)

Other supported environments

### FAX

ITU-T (CCITT) G3, Additional G3 (option) Compatibility Transmission speed (seconds)

AS/400® using OS/400 Host Print Transform, IBM iSeries

Modem speed: maximum (Kbps) 33.6

## PAPER HANDLING

Recommended paper size A4, A5, A6, B5, B6 Paper input: maximum (sheets) 2.300 Paper output: standard (sheets) 500 Paper weight (g/m²) 52 - 300

#### FCOLOGY

Power consumption: max. (kWh) Less than 1.85 Power consumption: sleep (W) 0.84 TEC (kWh) 2.6

#### **OPTIONS**

2x 550-sheet Paper tray, One-bin tray, Cabinet, Internal finisher, Punch kits, G3 Interface Unit, Fax connection unit, Fax memory, IEEE 802.11a/g/n, IEEE 1284 Interface, Bluetooth Interface, XPS Direct Print, Postscript3 (genuine), Camera Direct Print Card, File format converter, OCR unit, Enhanced security HDD, DataOverwriteSecurity Unit, NFC card reader, Smart Card Reader built-in unit, Device Server, Extended USB board, Key counter bracket, Counter interface, Memory Unit, ADF handle, Unicode Font Package for SAP, Paper Clamp

## CONSUMABLES

14,000 Toner: black (prints) Toner: cyan/magenta/yellow 12.000 (prints)

For availability of models, options and software, please consult your local supplier.



www.ricoh-europe.com





**PictBridge** 















RICOH @Remote

ISO9001 certified ISO14001 certified. ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2018 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.